SGT-P Replaceable Single-Gas Detector





Description

SGT-P is a single replaceable gas detector designed to detect oxygen deficiency and presence of toxic gas in the ambient environment. SGT-P is the replaceable type of a gas sensor and battery. When activated, SGT-P continuously monitors ambient air for the presence of a specific gas and alerts the user to potentially unsafe exposure with LED, vibrating, and audible alarms in the event that gas concentration exceeds alarm set points.

Key Feature

- Sensor and Battery Replacement
- Power on / off available

Sensor specification

• Configuration via exclusive IR Link

Specification

Model	SGT-P		
Sensor Type	Electrochemical		
Measurement	Diffusion type		
Display	LCD display		
Audible	90dB at 10cm		
Warning Lamp	Red Flashing LEDs (Light-Emitting Diode)		
Vibration	Vibration Alarm		
Battery	Manufacture: Vitzrocell / P/N: SB-AA02(P) / System: Lithium Primary Battery Nominal voltage: 3.6V / Nominal capacity: 1.2Ah		
Accuracy	±3%/Full Scale		
Temperature & Humidity	-40°C ~ +50°C(for Toxic) / -35°C ~ +50°C(for O2) 5% ~ 95% RH (non-condensing)		
Case	Rubber Enclosure		
Accessories	Calibration Cap, Manual, Test Report		
Option	External Sampling Pump (SP-Pump101), SENKO-IR Link, Docking Station		
Size & Weight	Size: 54mm(W) x 91mm(H) x 32mm(D) Weight: 93g(Toxic), 104g(O2) (Battery, clip included)		
Event Log	Recent 30 alarms		
Operating Life	24 months, based on 2 minutes of alarm per day		
Approval	ATEX II 1 G Ex ia IIC T4 Ga		
	IECEx Ex ia IIC T4 Ga		
	INMETRO Ex ja IIC T4 Ga		

Accessories



IR-Link Communication Connects to the computer in



order to program configuration and download data log



Sampling pump (SP-Pump101)



Extension Probe 5M/ 10M



SGT-P Docking Station

www.senko-detection.com

Gas	Measuring range	Low Alarm	High Alarm
02	0~30%Vol	19%Vol	23%Vol
со	0~500ppm	30ppm	60ppm
H2S	0~100ppm	10ppm	15ppm
H2	0~1000ppm	100ppm	500ppm
SO2	0~50ppm	2ppm	5ppm
NH3	0~100ppm	25ppm	35ppm
NO2	0~20ppm	3ppm	5ppm